

Aqua Prime 100% Acrylic DTM Primer White

PRODUCT DESCRIPTION:

Aqua Prime #15 is a specially formulated industrial acrylic primer designed for application to a variety of surfaces. Formulated from hybrid acrylic resins, it resists corrosion, is moisture resistant, alkali resistant and mildew resistant. Aqua Prime #15 Contains NO lead pigments, is chemical resistant and provides excellent coverage to the following properly prepared surfaces. The addition of 14 oz per gallon of Hy-Tech ceramic additive will provide an insulating, sound deadening barrier to the painted surface.

Aqua Prime #15 can be used on

*Aluminum *Galvanized Metal *Storage Tanks *Machinery *Metal Railings *Metal Trim
*Structural Steel *Metal Doors Wood Doors *Plaster *Masonry & Cementitious Surfaces

SURFACE PREPARATION:

The surface should be clean, dry, sound and free from all dirt, grease, oils, waxes, mildew and any other surface contaminants. Remove any loose scale, chalk or peeling paint. Previously painted steel surfaces should be prepared in accordance with the Steel Structures Painting Council specifications.

APPLICATION PROCEDURE:

Easily applied by brush, roller or spray, if using airless spray equipment the unit should be capable of 2500 psi with a .015-.019 fluid spray tip. Avoid application outside when weather conditions are threatening and late in the afternoon when there is a threat of moisture condensing on the wet paint. Apply when surface and ambient temperatures are above 55° F and below 90° F. Keep From Freezing!

APPROXIMATE COVERAGE: 350 sq.ft./gal.

PRECAUTIONS:

CAUTION: KEEP OUT OF REACH OF CHILDREN!

Keep away from sparks, heat and open flames.

USE WITH ADEQUATE VENTILATION! Avoid prolonged contact with skin and breathing of vapors. When spraying use an OSHA approved respirator. Use eye protection, wash thoroughly after handling and before eating or smoking. Close container after each use.

DO NOT TAKE INTERNALLY!

Produced by
Hy-Tech Industries
Brevard County Florida
"Home of the Kennedy Space Center"
Toll Free 1-866-744-4750
www.ceramicadditive.com